

**NATURAL RESOURCES CONSERVATION SERVICE
CONSERVATION PRACTICE STANDARD**

POND SEALING OR LINING – SOIL DISPERSANT TREATMENT

(No.)

CODE 521B

DEFINITION

A liner for a pond or waste impoundment consisting of a compacted soil-dispersant mixture.

PURPOSE

To reduce seepage losses from ponds or waste impoundments for water conservation and environmental protection.

CONDITIONS WHERE PRACTICE APPLIES

This practice applies where:

- Soils are suitable for treatment with dispersants
- Ponds or waste impoundments require treatment to reduce seepage rates and to impede the migration of contaminants to within acceptable limits

CRITERIA

General Criteria Applicable To All Purposes.

Dispersant treated soil liners shall comply with all federal, state, and local laws, rules, and regulations.

Lined structures shall meet all applicable NRCS standards. All inlets, outlets, ramps, and other appurtenances may be installed before, during, or after the liner placement, but shall be done in a manner that does not damage or impair the proper operation of the liner.

Dispersant treated soil liners shall be filter compatible with the natural foundation materials on which they are compacted according to NEH, Part 633, Chapter 26.

The minimum thickness of the finished compacted liner shall be 6 inches. The liner material shall be placed in layers not over 9 inches thick before compaction.

In addition to the treated blanket, at least 2 feet of fine-grained soil shall be placed over fractured rock outcrops or other highly permeable material.

The dispersant shall be tetrasodium pyrophosphate (TSPP), sodium tripolyphosphate (STPP), or soda ash unless laboratory tests using other dispersant types are used for design.

When laboratory permeability tests are required to determine application rates, the tests shall be performed using dispersant of the same quality and fineness as that proposed for use.

For protection against dispersant dust, personnel on site during dispersant application and mixing shall wear masks and goggles.

Criteria Applicable To Waste Impoundments

Design. Design of dispersant treated soil liners for waste impoundments shall be in accordance with AWMFH, Chapter 10, Appendix 10D, and/or state regulatory requirements.

Liner Protection. The liner shall be protected against desiccation cracking, the effects of water surface fluctuations, wave action, surface erosion, erosion from pipe inlets, agitation equipment, animals, or items installed through the liner. Protective measures shall be designed into the system to protect the liner for these cases. As a minimum, at least 6 inches of soil cover shall be placed over the soil-dispersant liner.

Criteria Applicable To Ponds

Application Rate. For ponds, in the absence of laboratory tests or field performance data on soils similar to those to be treated, the minimum application of dispersant per 6-inch thickness of constructed liner shall be:

Dispersant Type	Application rate (lb./ 100 ft ²)
Polyphosphates	7.5
Soda Ash	15

Liner Thickness. In the absence of more detailed testing and analyses, liner thickness shall be according to the following table:

Water Depth (feet)	Liner Thickness (inches)
8 or less	6
8.1 – 16	12
16.1 – 24	18
24.1 - 30	24

CONSIDERATIONS

Flattening the slopes of ponds or waste impoundments to facilitate compactive efforts during construction should be considered. The stair-step method of construction as outlined in AWMFH, Chapter 10, Appendix 10D may be considered in lieu of slope flattening.

A protective compacted soil cover should be considered for protecting the soil-dispersant liner for ponds.

Consider using a flexible membrane liner for sites that have water depths greater than 24 feet.

PLANS AND SPECIFICATIONS

The following list of Construction Specifications is intended as a guide to selecting the appropriate specifications for a specific project. The list includes most, but may not contain all, of the specifications needed for a specific project:

- IA-1 Site Preparation
- IA-3 Structural Removal
- IA-11 Removal of Water
- IA-21 Excavation
- IA-23 Earthfill
- IA-24 Drainfill
- IA-27 Diversions
- IA-45 Plastic (PVC, PE) Pipe
- IA-92 Fences

Plans and specifications for dispersant treated soil liners for ponds and waste impoundments shall be in keeping with this standard and shall describe the requirements for applying the practice to achieve its intended purpose. Plans and specifications shall include such drawings, specifications, material requirements, quantities, construction requirements, equipment requirements, and other documents as are necessary to describe the work to be done.

OPERATION AND MAINTENANCE

Maintenance activities required for this practice consist of those operations necessary to prevent damaging the treated soil liner. This includes, but is not limited to, excluding animals and equipment from the treated area, protection of the liner during initial filling, agitation, or pumping operations, and repair of disturbed or eroded areas.

REFERENCES

USDA-NRCS, National Engineering Handbook (NEH), Part 633, Chapter 26

USDA-NRCS, National Engineering Handbook (NEH), Part 651, Agricultural Waste Management Field Handbook (AWMFH)